









AquaRite® Pro Touch

AN EVOLUTION OF SALT CHLORINATOR **ACCORDING OUR TIME**

- · Salt chlorinator combined with water treatment controls
- · Available also in low salinity
- · Touch screen included
- From 3,2 gr salt/L for standard salinity and from 1,2 gr salt/L for low salinity
- Transparent cell with Hayward® T-Cell technology
- Automatic and continous pH and rX control
- Probe holder including prefilter of 65 microns.

INCLUDED















For easy and intuitive use





Transparent cell with Hayward® T-Cell technology





Peristaltic pump



WATER TREATMENT

Description	AQR-PROT-T3	AQR-PROT-T9	AQR-PROT-T15	AQR-PROT-T3LS
Chlorine production	10 g/h	20 g/h	30 g/h	Equiv 10 g/h
Pool size up to	60 m³	95 m³	150 m³	50 m³
Salt concentation	From 3,2 g/L			From 1,2 g/L

AQUARITE® PRO TOUCH

	Ciliotille production	10 g/11	20 g/11	30 g/11	Equiv 10 g/11	
	Pool size up to	60 m³	95 m³	150 m³	50 m³	
	Salt concentation	From 3,2 g/L			From 1,2 g/L	
	Display	Touch screen (4,3") removable screen for remote installation				
	pH control	Included with variable pH pump (1,5L/h - 7L/h)				
	rX control	Included (rX gold sensor)				
	Temperature	Included in the cell				
	Superchloration mode	Included (24 hours)				
	Manual adjustment of Cl	Configurable by gramage				
	Cover detection	Configurable production level 0-100% depending on open or closed pool cover				
	Flow switch	Mechanical with 3/4" connection				
	Self cleaning	Reverse polarity every 360 min				
	Protection	Flow switch				
	Alarms	AL3 for pH injection / AL4 for cell configurable				
_	Control box dimensions	270 x 220 x 120				

Description	AQR-PROT-T3	AQR-PROT-T9	AQR-PROT-T15	AQR-PROT-T3LS	
Cleaning base	GLX-CELLSTAND				
External temperature	T-OPTION-TEMP				
Pool Terre	KV02				